20K CAST STAINLESS STEEL, GLOBE VALVES

KITZ Fig:20UPAM

Sizes: 1/2-6inch(15-150mm)

Bolted Bonnet, Outside Screw & Yoke, Flanged Ends.

Standards

- · End to End: ASME B16.10 CLASS 300
- · End Connection: JIS B2220 20K
- · Wall Thickness: ASME B16.34 CLASS 300

Test Standard

KITZ STANDARD

Dimensions

SIZE(inch/mm)		L	Н	D1		
1/2	15	152.0	186.0	100.0		
3/4	20	178.0	186.0	100.0		
1	25	203.0	187.0	100.0		
11/2	40	229.0	236.0	160.0		
2	50	267.0	289.0	180.0		
21/2	65	292.0	297.0	200.0		
3	80	318.0	343.0	250.0		
4	100	356.0	398.0	300.0		
5	125	400.0	493.0	350.0		
6	150	444.0	564.0	400.0		

Material List


NAME OF PART	MATERIAL	SPECIFICATION	
BODY	STAINLESS STEEL	SCS14A	
BONNET	STAINLESS STEEL	SCS14A	
STEM	STAINLESS STEEL	SUS316	
DISC	STAINLESS STEEL	SUS316	
		SCS14A	

Specifications

20K CAST STAINLESS STEEL,GLOBE VALVES,Bolted Bonnet,Outside Screw & Yoke,Flanged Ends.

End to End:ASME B16.10 CLASS 300,End Connection:JIS B2220 20K,Wall Thickness:ASME B16.34 CLASS 300,Sizes: 1/2-6inch(15-150mm),BODY MATERIAL:STAINLESS STEEL,BONNET MATERIAL:STAINLESS STEEL,STEM MATERIAL:STAINLESS STEEL,DISC MATERIAL:STAINLESS STEEL,KITZ Fig:20UPAM





For more details, please refer to the drawing.

Pressure-temperature ratings and other performance data published in this catalog have been developed from our design calculation, in-house testing, field reports provided by our customers and/or published official standards or specifications. They are good only to cover typical applications as a general guideline to users of KITZ products introduced in this catalog. For any specific application, users are kindly requested to contact KITZ Corporation for technical advice, or to carry out their own study and evaluation for proving suitability of these products to such an application. Failure to follow this request could result in property damage and/or personal injury, for which we shall not be liable. Read instruction manual carefully before use.



